



T1880/T2080/T2380

SPECIFICATIONS

Specifications

Model		T1880	T2080	T2380
Engine:	Model	GH540V	GH710V	GH720V
	Type	OHV air-cooled gasoline engine		
	Number of cylinders	1	2	
	Total displacement	32.6 cu.in. (535 cc)	44.2 cu.in. (725 cc)	
	Gross horse power	18 HP (13.4 kW)*	20 HP (14.9 kW)*	23 HP (17.2 kW)*
	Starter	Electric start		
	Battery voltage:	12V		
Fuel tank capacity:	4 gal. (15.0 ℓ)			
Dimensions:	Overall length	72.8 in. (1850 mm)		
	Overall width [with mower]	54.8 in. (1392 mm)	60.8 in. (1544 mm)	
		[42" mower]	[48" mower]	
	Overall height	42.9 in. (1090 mm)	44.3 in. (1125 mm)	
Wheelbase:		50.8 in. (1290 mm)	54.3 in. (1380 mm)	
Wheel tread:	Front	30.8 in. (783 mm)		
	Rear	28.6 in. (727 mm)		
Tire size:	Front	15 × 6.00–6		
	Rear	22 × 11.00–10		
Weight:		617 lbs. (280 kg) (with 42" mower deck)	628 lbs. (285 kg) (with 48" mower deck)	
Turning radius (at outer front tire):		6.3 ft. (1.9 m)		
Uncut grass radius:		28.7 in. (0.73 m) (with 42" mower deck)	30.7 in. (0.78 m) (with 48" mower deck)	
Steering system:		Pinion & Sector gear type		
Number of speeds:		Infinite to maximum		
Traveling speed:	Forward	0 to 5.6 mph (0 to 9.0 km/h)		
Transmission:		Hydrostatic transmission		
PTO clutch:		Belt tension		
Brake:		Disc		
KRA system:		Standard		
Optional accessories:		Hour meter, Tractor cover, etc.		

Mower Specifications

Model	RCK42-LT20	RCK48-LT23
Mounting method	Suspended parallel linkage	
Adjustment of cutting height	Dial gauge	
Cutting width	42 in. (1067 mm)	48 in. (1219 mm)
Cutting height	1.0–4.0 in. (25 to 102 mm)	
Number of blades	2	
Discharge	Right side	

The company reserves the right to change the above specifications without notice.

This brochure is for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

* Manufacture estimate.