



Z300 Series



SPECIFICATIONS

Specifications

Model		ZG327		ZG332		ZD323		
		ZG327PA-60	ZG327RPA-60R	ZG332P-60	ZG332LP-72	ZD323-60		
Engine	Model	Kubota KGZ770-E2-MA1	Kubota KG770-E2-MA1	Kubota WG972-G-E3-ZG-1		Kubota D902-E3-ZD		
	Type	Gasoline, air-cooled V-Twin with heavy-duty canister air filter		Gasoline, liquid-cooled (3 cyl.)		Diesel, liquid-cooled (3 cyl.)		
	Max. horsepower (Gross)	27HP@3600 rpm		32.5HP@3600rpm		23HP@3200rpm		
	Total displacement	cu.in. (cc)	46.9 (768)		58.7 (962)		54.8 (898)	
	Starting system	Key switch					Key switch - super glow	
Dimensions	Overall length	in. (mm)	87.8 (2230)		91.7 (2329)	95.0 (2414)	87.4 (2220)	
	Overall width	(w/ mower)	in. (mm)	75.2 (1911)	63.1 (1604)	75.2 (1911)	87.6 (2224)	72.8 (1850)
		(w/o mower)	in. (mm)	57.5 (1460)				
	Overall height	(w/ ROPS upright)	in. (mm)	75.4 (1915)				
(w/ ROPS folded)		in. (mm)	61.2 (1555)		64.8 (1645)		61.2 (1555)	
Wheel base		in. (mm)	55.5 (1410)		52.5 (1333)	58.9 (1495)	55.5 (1410)	
Tread	Front	in. (mm)	38.4 (975)			42.1 (1070)	38.4 (975)	
	Rear	in. (mm)	45.3 (1150)					
Tire size	Front		15 x 6.0-6 Non-flat			15 x 6.0-6 Pneumatic		
	Rear		26 x 12.0-12					
Weight (w/ mower)	lbs. (kg)	1565 (710)		1651 (749)	1763 (800)	1645 (746)		
Transmission system	2-HST w/ Gear reduction							
Speed control	2-hand lever							
Travel speed range	Forward	mph (km/h)	0-10.6 (0-17.0)			0-9.3 (0-15.0)		
	Reverse	mph (km/h)	0-5.3 (0-8.5)			0-5.2 (0-8.3)		
Brake type	Wet multi disks, foot applied, released							
PTO	Type	Shaft drive						
	Clutch type	Hydraulic independent PTO clutch with wet multi disks						
	PTO brake	Wet single disk						
Mower deck	Model	RCK60P-327Z	RCK60P-331Z	RCK60P-327Z	RCK72P-332Z	RCK60P-331Z		
	Mower lift system	Hydraulic						
	Mower deck type	Pro commercial - Fabricated deck						
	Deck depth	in. (mm)	6.5 (165)	5.5 (140)	6.5 (165)			
	Belt type	Multi-Belt						
	Deck steel thickness	in. (mm)	0.17 (4.2)					
	Anti-scalp roller		Rigid	Swivel	Rigid	Swivel		
	Cutting width of mower		60 in.			72 in.	60 in.	
	Number of blades	3 blades						
	Cutting height	1 in. ~ 5 in. / 1/4 in. increments						
	Mounting system of mower	Quick joint, parallel linkage						
	Blade tip speed (max.)		18100 FPM	17100 FPM	18100 FPM	18200 FPM	18100 FPM	
	Engine stop system	Key stop						
Fuel tank capacity	gals. (ltrs.)	12.7 (48)				12.9 (49)		
Battery	U1L10 (12V, RC: 22 min., CCA: 300, CA: 365)			51R (12V, RC: 70 min., CCA: 475A)				
Alternator capacity	13.4 Amps at 12 Volts			14 Amps at 14 Volts				
Water temperature indicator	-			Standard				
Hour meter	Standard							
Fuel gauge	Electric							

The company reserves the right to change the above specifications without notice. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. For complete operational information, the operator's manual should be consulted.



Z300 Series



SPECIFICATIONS

Specifications

Model		ZD326			
		ZD326S-60	ZD326P-60	ZD326RP-60R	
Engine	Model	Kubota D1005-E3-ZD-2			
	Type	Diesel, liquid-cooled (3 cyl.)			
	Max. horsepower (Gross)	26HP @ 3200rpm			
	Total displacement	cu.in. (cc)	61.1 (1001)		
	Starting system	Key switch - super glow			
Dimensions	Overall length	in. (mm)	87.4 (2220)		
	Overall width	(w/ mower)	in. (mm)	75.2 (1911)	
		(w/o mower)	in. (mm)	57.5 (1460)	
	Overall height	(w/ ROPS upright)	in. (mm)	75.4 (1915)	
(w/ ROPS folded)		in. (mm)	61.2 (1555)		
Wheel base		in. (mm)	55.5 (1410)		
Tread	Front	in. (mm)	38.4 (975)		
	Rear	in. (mm)	45.3 (1150)		
Tire size	Front		15 × 6.0-6 Pneumatic	15 × 6.0-6 Non-Flat	
	Rear		26 × 12.0-12		
Weight (w/ mower)	lbs. (kg)	1667 (756)	1700 (771)	1667 (756)	
Transmission system		2-HST w/ Gear reduction			
Speed control		2-hand lever			
Travel speed range	Forward	mph (km/h)	0-9.3 (0-15.0)	0-10.6 (0-17.0)	
	Reverse	mph (km/h)	0-5.2 (0-8.3)	0-5.3 (0-8.5)	
Brake type		Wet multi disks, foot applied, released			
PTO	Type	Shaft drive			
	Clutch type	Hydraulic independent PTO clutch with wet multi disks			
	PTO brake	Wet single disk			
Mower deck	Model		RCK60P-331Z	RCK60R-331Z	
	Mower lift system		Hydraulic		
	Mower deck type		Pro commercial—Fabricated deck		
	Deck depth	in. (mm)	6.5 (165)	5.5 (140)	
	Belt type		Multi-Belt		
	Deck steel thickness	in. (mm)	0.17 (4.2)		
	Anti-scalp roller		Swivel		
	Cutting width of mower		60 in.		
	Number of blades		3 blades		
	Cutting height		1 in. ~ 5 in. / 1/4 in. increments		
	Mounting system of mower		Quick joint, parallel linkage		
	Blade tip speed (max.)		18100 FPM	17100 FPM	
Engine stop system		Key stop			
Fuel tank capacity	gals. (ltrs.)	12.9 (49)			
Battery		51R (12V, RC: 70 min., CCA: 475A)			
Alternator capacity		14 Volts at 14 Amps			
Water temperature indicator		Standard			
Hour meter		Standard			
Fuel gauge		Electric			

The company reserves the right to change the above specifications without notice. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. For complete operational information, the operator's manual should be consulted.



Z300 Series



SPECIFICATIONS

Specifications

Model		ZD331				
		ZD331P-60	ZD331LP-72	ZD331RP-60R		
Engine	Model	Kubota D1305-E3-ZD				
	Type	Diesel, liquid-cooled (3 cyl.)				
	Max. horsepower (Gross)	31HP @ 3000rpm				
	Total displacement	cu.in. (cc)	77.0 (1261)			
	Starting system	Key switch - super glow				
Dimensions	Overall length	in. (mm)	87.4 (2220)	91.9 (2335)	87.4 (2220)	
	Overall width	(w/ mower)	in. (mm)	75.2 (1911)	87.6 (2224)	63.1 (1604)
		(w/o mower)	in. (mm)	57.5 (1460)		
	Overall height	(w/ ROPS upright)	in. (mm)	75.4 (1915)		
(w/ ROPS folded)		in. (mm)	61.2 (1555)			
Wheel base		in. (mm)	55.5 (1410)	59.8 (1520)	55.5 (1410)	
Tread	Front	in. (mm)	38.4 (975)	42.1 (1070)	38.4 (975)	
	Rear	in. (mm)	45.3 (1150)			
Tire size	Front	15 x 6.0-6 Non-Flat				
	Rear	26 x 12.0-12				
Weight (w/ mower)	lbs. (kg)	1715 (778)	1770 (803)	1681 (763)		
Transmission system	2-HST w/ Gear reduction					
Speed control	2-hand lever					
Travel speed range	Forward	mph (km/h)	0-10.6 (0-17.0)			
	Reverse	mph (km/h)	0-5.3 (0-8.5)			
Brake type	Wet multi disks, foot applied, released					
PTO	Type	Shaft drive				
	Clutch type	Hydraulic independent PTO clutch with wet multi disks				
	PTO brake	Wet single disk				
Mower deck	Model	RCK60P-331Z	RCK72P-331Z	RCK60R-331Z		
	Mower lift system	Hydraulic				
	Mower deck type	Pro commercial—Fabricated deck				
	Deck depth	in. (mm)	6.5 (165)		5.5 (140)	
	Belt type	Multi-Belt				
	Deck steel thickness	in. (mm)	0.17 (4.2)			
	Anti-scalp roller	Swivel				
	Cutting width of mower	60 in.	72 in.	60 in.		
	Number of blades	3 blades				
	Cutting height	1 in. ~ 5 in. / 1/4 in. increments				
	Mounting system of mower	Quick joint, parallel linkage				
	Blade tip speed (max.)	18200 FPM		17100 FPM		
Engine stop system	Key stop					
Fuel tank capacity	gals. (ltrs.)	12.9 (49)				
Battery	51R (12V, RC: 70 min., CCA: 475A)					
Alternator capacity	14 Volts at 14 Amps					
Water temperature indicator	Standard					
Hour meter	Standard					
Fuel gauge	Electric					

The company reserves the right to change the above specifications without notice. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. For complete operational information, the operator's manual should be consulted.



Z300 Series



SPECIFICATIONS

Specifications

Model		ZP330P-60	
Engine	Model	Kubota WG972-GL-E3-ZG-1	
	Type	LPG, liquid-cooled (3 cyl.)	
	Max. horsepower (Gross)	31 HP@3600 rpm	
	Total displacement	58.7 cu.in. (962 cc)	
	Starting system	Key switch	
Dimensions	Overall length	91.7 in. (2329 mm)	
	Overall width	(w/ mower)	75.2 in. (1911 mm)
		(w/o mower)	66.1 in. (1679 mm)
	Overall height	(w/ ROPS upright)	75.4 in. (1915 mm)
(w/ ROPS folded)		64.8 in. (1645 mm)	
Wheel base		55.5 in. (1410 mm)	
Tread	Front	38.4 in. (975 mm)	
	Rear	45.3 in. (1150 mm)	
Tire size	Front	15 x 6.0-6 flat free	
	Rear	26 x 12.0-12	
Weight (w/ mower) (with LPG fuel tank)		1876 lbs. (851 kg)	
Transmission system		2-HST w/ Gear	
Speed control		2-hand lever	
Travel speed range	Forward	0-10.6 mph (0-17.0 km/h)	
	Reverse	0-5.3 mph (0-8.5 km/h)	
Brake type		Wet multi disks, foot applied, released	
PTO	Type	Shaft drive	
	Clutch type	Hydraulic independent PTO clutch with wet multi disks	
	PTO brake	Wet single disk	
Mower deck	Model	RCK60P-327Z	
	Mower lift system	Hydraulic	
	Mower deck type	Pro commercial— Fabricated deck	
	Deck depth	6.5 in. (165 mm)	
	Belt type	Multi-Belt	
	Deck steel thickness	0.17 in. (4.2 mm)	
	Anti-scalp roller	Rigid	
	Cutting width of mower	60 in.	
	Number of blades	3 blades	
	Cutting height	1 in. ~ 5 in. / 1/4 in. increments	
	Mounting system of mower	Quick joint, parallel linkage	
	Blade tip speed (max.)	18500 FPM	
Engine stop system		Key stop	
Fuel tank capacity		33.5 lbs x 2 (15.2 x 2 kg)	
Battery		51R (12 V, RC: 70 min., CCA: 475)	
Alternator capacity		14 Amps@14 Volts	

The company reserves the right to change the above specifications without notice. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. For complete operational information, the operator's manual should be consulted.